CopyCentre 265 shown with Duplex Automatic Document Feeder, High Capacity Feeder and Offset Catch Tray

WorkCentre 265 shown with Duplex Automatic Document Feeder, High Capacity Feeder and Office Finisher

WorkCentre 275 shown with Duplex Automatic Document Feeder, High Capacity Feeder and Advanced Office Finisher

WorkCentre Pro 275 shown with Duplex Automatic Document Feeder, High Capacity Feeder and Professional Finisher

	CopyCentre/WorkCentre/WorkCentre Pro 265	CopyCentre/WorkCentre/WorkCentre Pro 275
OUTPUT SPEED – printing and copying		
	Up to 65 ipm (images per minute) 8.5 x 11 in. (A4/210 x 297 mm)	Up to 75 ipm (images per minute) 8.5 x 11 in. (A4/210 x 297 mm)
	Up to 49 ipm 8.5 x 14 in. (216 x 356 mm)	Up to 49 ipm 8.5 x 14 in. (216 x 356 mm)
	Up to 42 ipm 11 x 17 in. (A3/297 x 420 mm)	Up to 42 ipm 11 x 17 in. (A3/297 x 420 mm)
FIRST-IMAGE-OUT TIME (FCOT) – letter size, from platen to offset catch tray		
	As fast as 2.7 seconds	As fast as 2.7 seconds

Copy Specifications

COPYING	
Document Scanner	Duplex Automatic Document Handler (DADH) 75-sheet capacity. Scans sizes up to 11 x 17 in. (A3/297 x 420 mm) SEF
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 9,999
Resolution	600 x 600 x 8 bit dpi input / 4800 x 1200 dpi interpolated output
Concurrency	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)
Copy Pre-Collation Memory (EPC)	256 MB — CopyCentre (expandable to 512 MB) 256 MB — WorkCentre (expandable to 512 MB) 512 MB — WorkCentre Pro

Continued

	Copy Specifications
COPYING *(Continued)*	
Basic Copy Features/Options	Collation Hole Punching Stapling Booklet Creation (Folding — V-fold only and Stapling) Automatic 2-Sided/Duplex Auto Reduction and Enlargement to fit selected paper size Auto Paper Select Auto Tray Switching
Imaging Copy Features/Options	Image Quality • Original Type Selections: Normal, Text, Halftone, Photo • Output Quality Selections: Lighter/Darker, Background Suppression, Contrast, Sharpness or Screening Book Copying/Bound Copying Edge Erase (with Print to Edge option) Mixed Size Original Image Shift (with Auto Center option)
Output Copy Features/Options	Transparencies (including dividers – blank or printed) Booklet Creation (Folding — V-fold only and Stapling) Multi-up (up to six columns by six rows) Invert Image (negative or mirror image) Covers (Front only, Front and Back, Back only: Blank or Printed) Annotation and Bates Stamping Build Job (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Inserts and Tab copying Sample Set and Job Storage (Store and Recall job programming) Heavy weight paper (not rough stock)
Other Copy/Device Features	Job Interrupt (Interrupt the current job) Help (Intuitive text and graphic descriptions) Internal Auditron (Copy) Languages (Select up to 20 languages for User Interface – US English, International English, International French, Italian, German, International Spanish, Dutch, Portuguese, Brazilian [Latin Portuguese], Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)
Reduction/Enlargement	Variable Zoom from 25% - 200% in 1% increments Six User-Programmable percentages (25%, 64%, 78%, 129%, 154% and 200%)
Foreign Device Interface (FDI) (Optional)	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service
USB Port	PC interface for upload/download of internal auditron data and Xerox Copier Assistant Customer device administration/software upgrade

Continued

	Copy Specifications
COPYING *(Continued)*	
Accessibility Option	Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.
PAPER HANDLING – Duplex Automatic Document Feeder (DADF) ***(optional)***	
Capacity*	75 sheets
Speed	265/275: Up to 75 ipm (images per minute), 8.5 x 11 in. (A4/210 x 297 mm) long edge feed (LEF)
Paper Sizes Sensed	Statement – 5.5 x 8.5 in. (A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF) Letter – 8.5 x 11 in. (A4/210 x 297 mm) LEF or SEF Legal – 8.5 x 14 in. (216 x 356 mm) SEF Ledger – 11 x 17 in. (A3/297 x 420 mm) SEF
Weights	13 lb to 32 lb bond (50 to 120 gsm)
PAPER HANDLING – Two Front Loading Paper Trays	
Capacity*	550 sheets each
Sizes	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Tab Stock Bond Envelopes Custom Settings (up to 7)

*Paper capacities are based on 20 lb bond (75 gsm, N. America / 80 gsm, Europe) stock; capacities will vary with different weight stocks.

	Copy Specifications
PAPER HANDLING – Bypass Tray	
Capacity*	100 sheets
Sizes	User Adjustable from 4.13 x 5.83 in. (105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Label Stock Transparencies Tab Stock Bond Envelopes Custom Settings (up to 7)
PAPER HANDLING – High Capacity Feeder (HCF)	
Capacity*	Two trays: 1,600 and 2,000 sheets each
Sizes	8.5 x 11 in. (A4/210 x 297 mm) LEF
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)
PAPER HANDLING – Total Capacity	
Device Total Capacity*	4,800 sheets (with Bypass tray, front loading paper trays and High Capacity Feeder)
OUTPUT OPTION – Offset Catch Tray (OCT) option	
Capacity*	300 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

*Paper capacities are based on 20 lb bond (75 gsm, N. America / 80 gsm, Europe) stock; capacities will vary with different weight stocks.

	Copy Specifications
OUTPUT OPTION – Office Finisher option	
Capacity*	Top Tray — 250 sheets Stacking Tray — 2,000 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Stapling*	50 sheets Single (any corner) and dual
Hole Punch (Optional)	2-hole punch (Europe) 3-hole punch (North America) 2-hole Legal punch (North America) 4-hole punch (Europe) 4-hole “Swedish” punch (Europe)
OUTPUT OPTION – Advanced Finisher option	
Capacity*	Top Tray — 250 sheets Stacking Tray — 3,000 sheets (2 x 1,500)
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Stapling*	50 sheets Single (any corner) and dual
Hole Punch	2-hole punch (Europe) - Standard 3-hole punch (North America) - Standard
Options	2-hole Legal punch (North America) 4-hole punch (Europe) 4-hole “Swedish” punch (Europe)
OUTPUT OPTION – Professional Finisher option	
Capacity*	Top Tray — 250 sheets Stacking Tray — 1,500 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Stapling*	50 sheets Single (any corner), dual, front, rear, SEF and 4-stitch

Continued

*Paper capacities are based on 20 lb bond (75 gsm, N. America / 80 gsm, Europe) stock; capacities will vary with different weight stocks.

Copy Specifications

OUTPUT OPTION – Professional Finisher option *(Continued)*

Hole Punch

2-hole punch (Europe) - Standard
3-hole punch (North America) - Standard

Options

2-hole Legal punch (North America)
4-hole punch (Europe)
4-hole "Swedish" punch (Europe)

Booklet Maker

Capacity*
- Tray stop up: 30 booklets (1-5 sheets per booklet)
- Tray stop down: Unlimited

Sizes
- Letter — 8.5 x 11 in. (A4/210 x 297 mm)
- Legal — 8.5 x 14 in. (216 x 356 mm)
- Ledger — 11 x 17 in. (A3/297 x 420 mm)

Weights
- 16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

Stapling*
- Saddle-stitch (2-15 sheets / 8-60 page booklet)

Folding
- V-folding (1-5 sheets / unstapled)

OUTPUT OPTION – Convenience stapler option ***(available only with shelf kit)***

Capacity*

50 sheets

MONTHLY DUTY CYCLE

265 – up to 250,000 pages
275 – up to 300,000 pages

BASIC CONFIGURATIONS**

CopyCentre, WorkCentre and WorkCentre Pro with DADF and HCF

ACCESSORY OPTIONS**

CopyCentre

Walkup Fax
- One line
- Two lines

Offset Catch Tray (OCT)
Office Finisher
Advanced Finisher
Professional Finisher
Convenience Stapler (available only with Shelf Kit)
Hole Punch (with Office Finisher — see Output Options for details)
256 MB Pre Collation Memory (EPC)
Foreign Interface Device (FDI)
Xerox Copier Assistant (XCA)
Upgrade Kits to WorkCentre or WorkCentre Pro

Continued

*Paper capacities are based on 20 lb bond (75 gsm, N. America / 80 gsm, Europe) stock; capacities will vary with different weight stocks.
**Features, configurations and options may vary by location.

Copy Specifications

ACCESSORY OPTIONS** *(Continued)*

WorkCentre *— same as CopyCentre, plus:*	Walkup Fax with LAN Fax • One line • Two lines PostScript 3 emulation/MAC Ethertalk Image Overwrite Security Email with LDAP/Authentication and additional memory
WorkCentre Pro *— same as CopyCentre and WorkCentre, plus:*	USB 2.0 (IEEE1284)/Parallel Port Kit Fax/Scan/Accounting Xerox Business Alliance Partner solutions FreeFlow Scan to PC Desktop SE and Professional Internet Fax

ELECTRICAL REQUIREMENTS

110-140 Volt Nominal, 60 Hz, 20A (North America)
220-240 Volt Nominal, 50 Hz, 10A (Europe)
Note: Convenience Stapler requires separate 110V 15A circuit

POWER CONSUMPTION[1]	*CopyCentre*	*WorkCentre / WorkCentre Pro*
Running	≤ 1690[1] watts	≤ 1740[1] watts
Standby	≤ 280 watts	≤ 310 watts
Low Power Mode	≤ 130 watts	≤ 160 watt
Auto Off / Sleep mode	≤ 5 watts	≤ 45 watts
Warm-up Ready to Copy	≤ 28 seconds	≤ 28 seconds
Warm-up Ready to Print	NA	≤ 130 seconds
Low Power Recovery	≤ 20 seconds	≤ 20 seconds

ENVIRONMENTAL CONSIDERATIONS

Required Temperature Range 10° to 32° C

Required Relative Humidity 10% to 85%

DIMENSIONS AND WEIGHTS *(CopyCentre)*	*Width*	*Depth*	*Height*[3]	*Weight*[2]
Configuration With OCT (265 only)	40 in. / 1,012 mm	28 in. / 710 mm	57 in. / 1,460 mm	275 lbs / 125 kg
With Office Finisher	50 in. / 1,271 mm	28 in. / 710 mm	57 in. / 1,460 mm	337 lbs / 153 kg
With Advanced Office Finisher	56 in. / 1,412 mm	28 in. / 710 mm	57 in. / 1,460 mm	443 lbs / 201 kg
With Professional Finisher	58 in. / 1,477 mm	28 in. / 710 mm	57 in. / 1,460 mm	443 lbs / 201 kg

[1] With Office Finisher. [2] Weights do not include Rear Wall (3.78 lbs. / 1.72 kg) or Shelf (2.99 lbs. / 1.36 kg). [3] Height with DADH raised.

Copy Specifications

DIMENSIONS AND WEIGHTS (WorkCentre / WorkCentre Pro)	Width	Depth	Height [3]	Weight [2]
Configuration With OCT (265 only)	51 in. / 1,297 mm	34 in. / 875 mm	57 in. / 1,460 mm	295 lbs / 134 kg
With Office Finisher	61 in. / 1,556 mm	34 in. / 875 mm	57 in. / 1,460 mm	358 lbs / 162 kg
With Advanced Office Finisher	67 in. / 1,697 mm	34 in. / 875 mm	57 in. / 1,460 mm	463 lbs / 210 kg
With Professional Finisher	69 in. / 1,762 mm	34 in. / 875 mm	57 in. / 1,460 mm	463 lbs / 210 kg

SPACE REQUIREMENTS *(Fixed)*	Width	Depth		Height
Configuration With OCT (265 only)	119 in. / 3,023 mm	CopyCentre WorkCentre/ WorkCentre Pro	107 in. /2,718 mm 108 in. /2,743 mm	78 in. / 1,981 mm
With Office Finisher	129 in. / 3,276 mm	CopyCentre WorkCentre/ WorkCentre Pro	107 in. /2,718 mm 108 in. /2,743 mm	78 in. / 1,981 mm
With Advanced Office Finisher	134 in. / 3,403 mm	CopyCentre WorkCentre/ WorkCentre Pro	107 in. /2,718 mm 108 in. /2,743 mm	78 in. / 1,981 mm
With Professional Finisher	137 in. / 3,480 mm	CopyCentre WorkCentre/ WorkCentre Pro	107 in. /2,718 mm 108 in. /2,743 mm	78 in. / 1,981 mm

SPACE REQUIREMENTS *(Moveable)*	Width	Depth		Height
Configuration With OCT (265 only)	79 in. / 2,012 mm	CopyCentre WorkCentre/ WorkCentre Pro	67 in. /1,702 mm 68 in. /1,735 mm	78 in. / 1,981 mm
With Office Finisher	89 in. / 2,271 mm	CopyCentre WorkCentre/ WorkCentre Pro	67 in. /1,702 mm 68 in. /1,735 mm	78 in. / 1,981 mm
With Advanced Office Finisher	95 in. / 2,412 mm	CopyCentre WorkCentre/ WorkCentre Pro	67 in. /1,702 mm 68 in. /1,735 mm	78 in. / 1,981 mm
With Professional Finisher	98 in. / 2,477 mm	CopyCentre WorkCentre/ WorkCentre Pro	67 in. /1,702 mm 68 in. /1,735 mm	78 in. / 1,981 mm

CERTIFICATIONS

FCC Class A Compliant (US), DOC Class A Compliant (Canada)
89/336/EEC (Europe)
UL Listed (UL 1950, Third Edition)
CB Certified (IEC 60950/EN 60950)
73/23/EEC (Europe)
95/5/EEC (Europe)
Energy Star
Blue Angel

SUPPLIES

Description	Order Number	No. per Box	Expected Yield
Toner Cartridge	6R01146	2	45,000 at 6% area coverage
Waste Toner Bottle (supplied with each toner cartridge box)		1	100,000
Staple Cartridge (for Office Finisher/Advanced Office Finisher)	108R00493	3	5,000 per cartridge (15,000 staples)

Continued

[1] With Office Finisher. [2] Weights do not include Rear Wall (3.78 lbs. / 1.72 kg) or Shelf (2.99 lbs. / 1.36 kg). [3] Height with DADH raised.

Copy Specifications

SUPPLIES *(Continued)*	*Description*	*Order Number*	*No. per Box*	*Expected Yield*
	Staple Cartridge (for Booklet maker saddle-stitch stapling)	8R12897	8 (4 x 2)	2,000 per cartridge (16,000 staples)
	Staple Cartridge (for Convenience Stapler) • Complete Cartridge • Refill Cartridge	 8R12964 8R12941	 3	 5,000 per cartridge (15,000 staples)
	Fuser Module (includes ozone filter)	109R00723	1	400,000
	Xerographic Module - Metered	113R00672	1	400,000
	Xerographic Module - Sold	113R00674	1	400,000
	Document Handler Feeder Rolls	113R00686	1	150,000 feeds

Print Specifications

NETWORK PRINTING – SMart Controller *(Simultaneous rip, receive, program ahead, queue processing, and transmit)*

Processor	1 GHz AMD Duron dedicated
Memory (ESS)	WorkCentre 128 MB (expandable to 256MB), WorkCentre Pro 256 MB
System Disk	80 GB Hard Drive shared
Printer Language (PDL) auto switching	WorkCentre • PCL 6/PCL 5e • PostScript 3 emulation (Optional) WorkCentre Pro • PCL 6/PCL 5e • PostScript 3 emulation • TIFF (6.0 Old JPEG and New JPEG) • TIFF Fax Extended (TIFF - FX) • PDF • LCDS, SCS, XES and IPDS through third party transforms

NETWORK PRINTING – Resolution *(printing via CentreWare software)*

PostScript emulation: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey)
PCL: 600 x 600 dpi
Supports PCL and PS switching within job

NETWORK PRINTING – Printing Features

Bi-directional Print Drivers
Embedded web server for remote control/monitor/setup
Job monitoring at the device and at desktop

Advanced Features Include:
PS
Special font
Banner Sheet
Rotate Image
Offset

Continued

Print Specifications

NETWORK PRINTING – Printing Features *(Continued)*

Paper Output

Job Type
- Secure, Sample, Delay
- LAN Fax-with fax option

Paper Selection by attribute (including transparency separators)
Duplex (2-sided)
Finishing
- Stapling positions
- Hole punch with option
- Booklet creation with Professional finisher
- Fit to new paper size
- Saddle stitch

Output tray selections
Store and recall driver setting

Special Pages

Page level programming (covers, inserts/tabs, exception pages)

Image Options

Light/Dark
Toner saver
Resolution options (600 x 600 and 1200 x 1200 dpi)
Reduction/Enlargement
Margins (edge to edge printing)
Invert Image (negative/mirror)

Layout/Watermark

N-up (16)/Multi-up
Booklet Layout/Finishing
Fit to new paper size
Image orientation
Watermark options

PRINT PROTOCOLS AND NETWORKS

Physical

Ethernet 10/100BaseT, 10BaseT, 10Base2 (IEEE802.5) (Token ring) –via adapter, wireless Ethernet (IEEE802.11a/b/g) -via third party adapter
USB 2.0 (IEEE1284)/Parallel Port Kit (WorkCentre Pro option)

Operating Systems

WorkCentre
- Microsoft Windows 98, Me, NT 4.0, 2000, XP, Windows Server 2003, Citrix, Novell NetWare 4.x, 5.x, 6

WorkCentre Pro
- Microsoft Windows 98, Me, NT 4.0, 2000, XP, Windows Server 2003, Citrix, Novell NetWare 4.x, 5.x, 6
- Mac OS 8.x, 9.x, OS X, 10.3 and higher
- Solaris 2.8, 2.9, 2.10
- HPUX 11.0
- IBM AIX 4.3.3
- Linux Fedora Core 1 (Intel)
- Linux Yellowdog 3.0

Print Specifications

PRINT PROTOCOLS AND NETWORKS *(Continued)*

Network Protocols	WorkCentre (without PS) • TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP, NDPS®/NEPS WorkCentre Pro • TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP, NDPS®/NEPS • AppleTalk/EtherTalk, Bonjour		
Administration Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP v2, HTTP, RARP, DHCP Autonet		
Security Protocols/Features	HTTPS, IPsec, IP filtering Unlimited Secure Print, Audit log, Image Overwrite (optional)		
Fonts	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (true type fonts) PostScript 3: 136 PostScript standard fonts (true type fonts/send fonts as/substitution table) Font Management Utility for downloading additional fonts (available for Windows and Mac)		
Print Drivers	***Environment***	***PCL6/5e***	***PostScript 3***
	Windows 98/Me, NT 4.0, 2000/XP, Windows Server 2003, Windows Walk-up (PS), Microsoft Certified	Bi-directional features (Xerox custom graphical user interface) • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs	Bi-directional features (Xerox custom graphical user interface) • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs
	Macintosh System 8.x – 10.2	N/A	Generic PPD Bi-Directional via AppleTalk (9.x)
	Macintosh System 10.3 and higher	N/A	Bi-directional features (Xerox custom graphical user interface) • Watermark, booklet creation, JBA, secure, sample, delay print and LAN Fax (option)

Print Specifications

PRINT PROTOCOLS AND NETWORKS *(Continued)*

Print Submission Tools	*Environment*	*PCL*	*PostScript 3*
	Solaris 2.8, 2.9, 2.10; HPUX 11.0, IBM AIX 4.3.3; Linux Fedora Core 1 (Intel); Linux YellowDog 3.0	Submission Tool only	Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows 98/Me/NT 4.0/2000/XP, Windows Server 2003	Submission Tool for any TIFF or PDF file	N/A

DEVICE MANAGEMENT

Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2
Xerox CentreWare Internet Services	Allows simple remote installation setting of configuration options and management of the device
Xerox CentreWare Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher
NovelI NDPS/NEPS (gateway for WorkCentre Pro)	Server gateway application: centralized management tool
Xerox CentreWare for Unicenter TNG	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre Pro under a Unicenter TNG Business Process View
Xerox CentreWare for Tivoli NetView	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction systems in the general discovery performed by Tivoli NetView
Xerox CentreWare for HP OpenView	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
Xerox Barcode Pro PS (optional) Purchase via www.font.net	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.

Continued

Print Specifications

DEVICE MANAGEMENT *(Continued)*

Xerox Device Types for SAP R/3 Environment are available at www.xeroxofficesapsolutions.com	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre Pro printing functionality (PostScript and PCL): • One- to Two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • # of copies – provide the ability to print multiple copies • Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc. • Print security via PIN ID capability at the WorkCentre Pro • Job Based Accounting (JBA) – Provides capability to add JBA UserIDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net
Xerox SAP R/3 Intelligent Barcode Utility (optional) Purchase via www.font.net	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string, and data compression.

CENTREWARE INTERNET SERVICES – Integrated device Web page

Device Status	Web server embedded on SMart Controller • Tray status/contents • Consumables status • Alerts
Job-Print Queue Viewing	Complete job print queue management –delete
Job Submission	Print ready files PS, PCL (TIFF, PDF with WorkCentre Pro only) Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Scan Template Management	250 templates can be created Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning
Browsers	Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x Safari 1.x Mozilla Firefox 1.x
Support	Online support available via web page

Scan Specifications

NETWORK SCANNING WITH EMAIL *(Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services)*

Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs
Input Speed	Scan at 75 ipm 265/275 - 8.5 x 11 in. (A4/210 x 297 mm) LEF at all resolutions
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
Capability for WorkCentre - optional (scan to email only)	Scan to email (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients)
Capability for WorkCentre Pro - standard	Scan to email (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients) Scan to file Scan to network server / directory Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from www.xerox.com
Authentication	Secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) Optional PIN-based guest login
Network Protocol	***Network Scanning*** Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS ***Email*** SMTP MIME encoded
File Formats	TIFF 6.0 with G3 MH, G4 MMR, MRC or JPEG compression (single page or multiple pages) PDF (image only with G3 MH, G4 MMR, JPEG or JBIG2 compression)
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: • 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template - Metadata Fields consists of field name, display at the LUI or not, default value and other configurations Customized fields viewed on user interface Variable data entered using virtual keyboard at device Scan to network server/directory

Continued

	Scan Specifications
NETWORK SCANNING WITH EMAIL *(Continued)*	
Scan Template Management	Share scan templates among WorkCentre Pro via device cloning Scan template management (250 templates) with CentreWare Internet Services Share scan templates via device cloning Select confirmation sheet option
Scan Features	Build job (for scan to file only)(enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options, scan to edge.
NETWORK SCANNING SOFTWARE OPTIONS with WorkCentre Pro	
Supported Scan Destinations –scan template creation (Varies by scanning software options purchased)	Scan to application (workflow, Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web folders Scan to Web URL Scan to remote printer Scan to PC Desktop (SE and Professional editions)
FreeFlow SMARTsend (optional)	Server base document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per device) Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary) • Scan to File Destinations: email, Microsoft NetWare folder, network folder, FTP, Microsoft Exchange 2000 web folders, web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint Workflow initiation via device scanning user interface (template selection at device UI)
FreeFlow SMARTsend Professional (optional)	Everything in Free Flow SMARTsend, plus: • Workflow initiation via Paperware (Scan coversheets) • Server-based Optical Character Recognition (OCR) • Adding of Metadata information • Scan to Internet fax file destination
FreeFlow Scan to PC Desktop SE (optional)	A desktop offering that provides document imaging, archiving, editing and organization tools ScanSoft PaperPort SE 10 – image viewing and file management software ScanSoft OmniPage SE 3.0– offer desktop/client installation – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre Pro to individual desktops
FreeFlow Scan to PC Desktop Professional (optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools. ScanSoft PaperPort Professional 10 image viewing and file management software • Complete PDF functionality • Secure PDF workflow of all scanning applications ScanSoft OmniPage Pro 14 Office (for desktop/client installation) Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre Pro to individual desktops. Also includes an email inbox polling capability

Fax Specifications

FAX OPTIONS –Walk-up option *(One or Two Lines options)*

Compatibility	ITU (CCITT) Group 3
Memory	32MB – One Line 256MB- Two Line
Speed/Modem(s)	1 or 2 V.34 modems: 33,600bps. Less than 4 seconds per page transmission time, ISDN via third party adapter
Compression/Speed	MH/MR/MMR/G3/Super G3
Fax Send Features	Quality/Resolution • Original type: Normal, text, half tone, photo, lighter/darker, background suppression • Fax - off Platen, mixed sizes or Bound/Book Auto Send (Up to 5) Audio line monitor Transmission options (Report/Header) Reduce/Split large documents Cover letter Delayed send Build Job (up to 1000 images) Polling
Fax Receive Features	One or two-sided printing Stapled or unstapled, hole punch Receive print mode --Manual (size, margin, stock, header)/Auto Auto answer delay Secure receive Junk fax prevention
Fax Reports	Activity Dial directory Group directory Options Pending Jobs
Fax Mailboxes	Up to 100 password-protected Poll Remote mailboxes (up to 255) password-protected
Auto Dialing Features	Speed Dials • 200 (One-line option) • 1,000 (Two-line option) Group Dials • Up to 100 groups with up to 200 recipients per group (One-line option) • Up to 200 groups with up to 400 recipients per group (Two-line option) Auto redial • Up to 14 attempts • Up to 25 min intervals • Batch Send (up to memory capacity)
Resolutions	200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi (Super fine) 200 x 400 dpi 400 x 400 dpi 400 x 600 dpi 600 x 600 dpi

Fax Specifications

FAX OPTIONS - LAN Fax with Walkup Fax *(Optional with WorkCentre and WorkCentre Pro)*

Driver based LAN fax for Windows and Macintosh users (PCL and PS drivers)
Recipient options (add recipient or add from phone book)
User personal phone book – up to 1,000 entries
Confirmation sheet
Send speed (14.4/33.6kbps or 4800bps)
Send time
Dialing options (prefix or credit card)
Cover sheet (add notes)
Preferences – Phonebook (personal or shared LDAP)

FAX OPTIONS – Internet Fax *(Optional with WorkCentre Pro)*

Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003) Novell over IP/IPX (Netware 4.x/5.x/6.x) Optional PIN-based guest login
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 100 x 100 dpi 72 x 72 dpi
Network Protocols	SMTP POP3 (RFC 1939)
Compliance	ITU-T T.37 complaint
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body

Fax Specifications

FAX OPTIONS – Network Fax Server Integration *(Optional with WorkCentre Pro)*	
Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration (via SMTP).
Maximum Scan Size	11 x 17 in. (A3/297 x 420mm)
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003) Novell over IP/IPX (Netware 4.x, 5.x, 6.x) Optional PIN-based guest login
Network Protocols	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. (A3/297 x 420 mm) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, seven levels of contrast, seven levels of sharpness)
Fax Print Features	One – or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Business Alliance Partner Program. For details visit www.xerox.com

Other Specifications

ACCOUNTING OPTIONS – Internal Auditron	
Tracking	Copy usage
Accounting	Up to 2,150 User accounts Up to 5,925 General accounts Up to 256 Group accounts
Features	Auditron report printout, ability to upload/download account and usage data via direct connection using Microsoft Windows based software
ACCOUNTING OPTIONS – Xerox Standard Accounting *(Standard with WorkCentre and WorkCentre Pro)*	
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,500 User accounts (User Id) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.
ACCOUNTING OPTIONS – Job Based Accounting – 3rd Party *(Optional with WorkCentre Pro)*	
	Enhanced network accounting with up to the minute data on how the WorkCentre Pro system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Business Alliance Partner solutions. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support WCP requests account authentication from 3rd party server enabling larger databases of users and accounts

ENERGY STAR

© 2005 Xerox Corporation. All rights reserved. XEROX®, CentreWare®, WorkCentre® Pro and Copier Assistant are trademarks of Xerox Corporation. PostScript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Product information and/or specifications are subject to change without notice. 06/05 610P723070 W7XSS-01UA